

20•20MW, 20•20W

COMPANION HOLDING CABINET





MODEL 20*20MW (SHOWN WITH RIGHT-HAND DOOR AND OPTIONAL PAN TROLLEY)



MODEL 20°20W (SHOWN WITH RIGHT-HAND DOOR AND OPTIONAL PAN TROLLEY)

- ecosmart®
 - HALO HEAT . . . a controlled, uniform heat source that gently surrounds food to provide a better appearance, taste, and longer holding life.
 - Uses one-third to one-half the energy of conventional holding equipment.
 - Motionless air inside cabinet prevents transfer of flavors, retains more product moisture, and preserves color.
 - Close temperature tolerance, along with even heat distribution, maintains an ideal serving temperature throughout the cabinet.
 - Available in a stationary or mobile cabinet design.
 - Optional Roll-In Pan Cart (trolley) is designed for maximum capacity and is completely interchangeable with the Combitherm® CombiOven™ electric model 20•20es, or gas model 20•20EsG, and the Alto-Shaam Quickchiller™ QC-100.

Insulated Halo Heat companion holding cabinet features 20 gauge stainless steel construction. The cabinet is controlled with one (1) ON/OFF power switch and an adjustable, electronic thermostat which includes a heat indicator light, temperature set button, and temperature increase and decrease buttons. The thermostat has a range of 60° to 205° F (16° to 96° C) and includes a digital display indicating the air temperature within the cabinet. The door has a heavy duty rotary handle with standard left-hand hinging.

Optional Roll-In Pan Cart (trolley) features removable handle, pan support rails to hold twenty-four (24) full-size pans, and six (6) stainless steel wire shelves for sheet pans. Cart includes two (2) rigid casters and two (2) swivel casters with brake.

- ☐ MODEL 20 20 MW: Mobile holding cabinet supported by four (4) heavy duty casters
- ☐ MODEL 20 20W: Stationary holding cabinet supported by four (4) heavy equipment legs

FACTORY INSTALLED OPTIONS

- Left-hand door swing is standard.
- ☐ Specify right-hand door as a special order.













MODEL 20.20MW WITH



OPTIONAL ROLL-IN



OPTIONAL ROLL-IN
PLATE CART




PRINTED IN U.S.A.


W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A. PHONE: 262.251.3800 800.558.8744 U.S.A./CANADA FAX: 262.251.7067 800.329.8744 U.S.A. ONLY



20•20MW, 20•20W







WEIGH	Т					
NET	ET 378 lb (171mm)					
SHIP	513 lb (233 kg)					
CARTON DIMENSIONS: (L X W X H)						
53" x 53" x 87"						
(1364mm x 1364mm x 2210mm)						

INSTALLATION REQUIREMENTS

Cabinet must be installed level. It must not be installed in any area where it may be affected by steam, grease, dripping water, high temperatures, or any other severely adverse conditions.

CLEARANCE REQUIREMENTS

3" (76mm) at the back, 2" (51mm) at the top, and 1" (25mm) at both sides

DIMENSIONS:	$(H \times W \times D)$
EXTERIOR:	

73-5/8" x 35" x 41-9/16" (1869mm x 888mm x 1056mm)

INTERIOR:

59-1/4" x 25-5/16" x 33-45/16" (1505mm x 642mm x 861mm)

ELECTRICAL							
VOLTAGE	PHASE	CYCLE/HZ	AMPS	kW	CORD & PLUG		
208-240 (AGC	y) 1	50/60	16.0	3.8	NEMA 6-20P		
208	1	50/60	13.9	2.9	20A-250V Plug		
240	1	50/60	16.0	3.8			
230	1	50/60	15.3	3.5	NO CORD OR PLUG		

PRODUCT\PAN CAPACITY

480 lbs (218 kg) MAXIMUM

VOLUME MAXIMUM: 300 QUARTS (284 LITERS)

OPTIONAL ROLL-IN PAN CART:

FULL-SIZE PANS: Forty (40) 20" x 12" x 2-1/2" MAXIMUM

GN 1/1: Forty (40) (530mm x 325mm x 65mm) GN 2/1: Twenty (20) (650mm x 530mm x 65mm)

FULL-SIZE SHEET PANS: Ten (10) 18" x 26" x 1"

Twenty (20) with added shelves

OPTIONS & ACCESSORIES

5007925 ☐ Preheat Sealing Strip

□ Roll-In Pan Cart (fits 20•20ES, 20•20ESG & QC-100)

65-11/16" x 28-1/8" x 35-5/16"

(1668mm x 714mm x 896mm)

TEN (10) STAINLESS STEEL WIRE SHELVES

TWENTY (20) PAN SUPPORT RAIL POSITIONS

2-5/8" (67mm) VERTICAL SPACING BETWEEN RAILS

21-3/16" (538mm) HORIZONTAL WIDTH BETWEEN RAILS

UN-27971 ☐ Roll-In Plate Cart (fits 20 • 20ES, 20 • 20ESG & QC-100)

65-15/16" x 28-1/8" x 39-13/16"

(1673mm x 714mm x 1011mm)

2-11/16" (69mm) SPACING

HOLDS 108 10-12" (254-305mm) DIAMETER PLATES

☐ Roll-In Plate Cart (fits 20 • 20ES, 20 • 20ESG & QC-100) UN-28311

65-1/2" x 30-5/16" x 39-9/16" (1663mm x 770mm x 1004mm)

3-1/2" (89mm) SPACING

HOLDS 78 10-12" (254-305mm) DIAMETER PLATES

☐ Shelf, Stainless Steel Wire

SH-22473

UN-27970



W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A. PHONE: 262.251.3800 800.558.8744 U.S.A./CANADA