



FACTORY INSTALLED OPTIONS:

- Bottom perimeter bumper
- 8" (203) one-piece vertical handle (except 4 stack) - see page 72
- Group 2 laminate exterior - see page 121

ACCESSORIES (PAGE 75):

- Stainless Steel Dish Covers



Lakeside's award-winning mobile heated cabinet gives you the flexibility to distribute heated plates at point of service.



Freight Class: **92.5**
Ships in: **5** days or less!

HEATED | STAINLESS STEEL



Model	Accom. Plate Size	Overall Size				Case Weight Lbs. (Kg)	Case Cube Cu. ft. (m³)
		W	L	H	(W L H)		
1 Stack - Heated							
6100	Up to 5" (Up to 127)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	93 (42.1)	17.5 (.48)
6105	5-1/8" to 5-3/4" (130 to 146)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	93 (42.1)	17.5 (.48)
6106	5-7/8" to 6-1/2" (149 to 165)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	95 (42.8)	17.5 (.48)
6107	6-5/8" to 7-1/4" (168 to 184)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	98 (44.1)	17.5 (.48)
6108	7-3/8" to 8-1/8" (187 to 206)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	105 (47.3)	17.5 (.48)
6109	8-1/4" to 9-1/8" (210 to 232)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	110 (49.5)	17.5 (.48)
6110	9-1/4" to 10-1/8" (235 to 257)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	115 (51.8)	17.5 (.48)
6111	10-1/4" to 11" (260 to 279)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	115 (51.8)	17.5 (.48)
6112	11-1/4" to 12-1/4" (286 to 311)	18-1/2"	22-1/2"	39-7/8"	(470 571 1013)	122 (55.0)	17.5 (.48)
2 Stack - Heated							
6200	Up to 5" (Up to 127)	18-1/2"	32"	39-7/8"	(470 813 1013)	100 (45.2)	19.5 (.54)
6205	5-1/8" to 5-3/4" (130 to 146)	18-1/2"	32"	39-7/8"	(470 813 1013)	100 (45.2)	19.5 (.54)
6206	5-7/8" to 6-1/2" (149 to 165)	18-1/2"	32"	39-7/8"	(470 813 1013)	103 (46.7)	19.5 (.54)
6207	6-5/8" to 7-1/4" (168 to 184)	18-1/2"	32"	39-7/8"	(470 813 1013)	106 (48.1)	19.5 (.54)
6208	7-3/8" to 8-1/8" (187 to 206)	18-1/2"	32"	39-7/8"	(470 813 1013)	117 (53.1)	19.5 (.54)
6209	8-1/4" to 9-1/8" (210 to 232)	18-1/2"	32"	39-7/8"	(470 813 1013)	121 (54.9)	19.5 (.54)
6210	9-1/4" to 10-1/8" (235 to 257)	18-1/2"	32"	39-7/8"	(470 813 1013)	125 (56.7)	19.5 (.54)
6211	10-1/4" to 11" (260 to 279)	20-3/4"	36-1/2"	39-7/8"	(527 927 1013)	138 (62.6)	24.4 (.67)
6212	11-1/4" to 12-1/4" (286 to 311)	20-3/4"	36-1/2"	39-7/8"	(527 927 1013)	138 (62.6)	24.4 (.67)
3 Stack - Heated							
6300	Up to 5" (Up to 127)	18-1/2"	46-3/8"	39-7/8"	(470 1178 1013)	171 (77.4)	28.0 (.77)
6305	5-1/8" to 5-3/4" (130 to 146)	18-1/2"	46-3/8"	39-7/8"	(470 1178 1013)	171 (77.4)	28.0 (.77)
6306	5-7/8" to 6-1/2" (149 to 165)	18-1/2"	46-3/8"	39-7/8"	(470 1178 1013)	176 (80.0)	28.0 (.77)
6307	6-5/8" to 7-1/4" (168 to 184)	18-1/2"	46-3/8"	39-7/8"	(470 1178 1013)	180 (81.8)	28.0 (.77)
6308	7-3/8" to 8-1/8" (187 to 206)	18-1/2"	46-3/8"	39-7/8"	(470 1178 1013)	192 (87.3)	28.0 (.77)
6309	8-1/4" to 9-1/8" (210 to 232)	18-1/2"	46-3/8"	39-7/8"	(470 1178 1013)	196 (89.1)	28.0 (.77)
6310	9-1/4" to 10-1/8" (235 to 257)	18-1/2"	46-3/8"	39-7/8"	(470 1178 1013)	200 (90.9)	28.0 (.77)
4 Stack - Heated							
6400	Up to 5" (Up to 127)	32"	32"	39-7/8"	(813 813 1013)	188 (85.4)	33.0 (.91)
6405	5-1/8" to 5-3/4" (130 to 146)	32"	32"	39-7/8"	(813 813 1013)	188 (85.4)	33.0 (.91)
6406	5-7/8" to 6-1/2" (149 to 165)	32"	32"	39-7/8"	(813 813 1013)	192 (87.3)	33.0 (.91)
6407	6-5/8" to 7-1/4" (168 to 184)	32"	32"	39-7/8"	(813 813 1013)	193 (87.3)	33.0 (.91)
6408	7-3/8" to 8-1/8" (187 to 206)	32"	32"	39-7/8"	(813 813 1013)	220 (100.0)	33.0 (.91)
6409	8-1/4" to 9-1/8" (210 to 232)	32"	32"	39-7/8"	(813 813 1013)	222 (100.1)	33.0 (.91)
6410	9-1/4" to 10-1/8" (235 to 257)	32"	32"	39-7/8"	(813 813 1013)	225 (102.3)	33.0 (.91)

Measurements in () denote metric millimeters, unless otherwise specified. Lake-Glide® Casters: 4" (102) - All swivel, 2 ea. w/brake, extra-load. Heated Models include 6' (1829) coiled cord with 5-15P NEMA except Models 6409 & 6410, which include 5-20P plug for 120 V. Group 2 laminate exterior - see page 121.

ELECTRICAL SPECIFICATIONS

Model #6106, #6206	300 W	2.5 A	120 V	Model #6309, #6310	1350 W	11.3 A	120 V
Model #6107, #6108, #6109, #6110, #6111	450 W	3.8 A	120 V	Model #6406, #6407, #6408	1200 W	10.0 A	120 V
Model #6112, #6207, #6208, #6209, #6210, #6211	900 W	7.5 A	120 V	Model #6409, #6410	1800 W	15.0 A	120 V
Model #6212, #6306, #6307, #6308	900 W	7.5 A	120 V				

208 / 240V, 60 Hz; 220V, 50 Hz also available, please specify.