

**ADJUST-A-FIT® PLATE DISPENSER CABINETS – HEATED/NON-HEATED | STAINLESS STEEL**

Hold a variety of different size plates in the same cabinet for ultimate award-winning flexibility.

- Choose up to four plate stacks to conveniently hold varying sizes and number of plates
- Each heated dispenser features its own thermostatic control to manage and adjust temperature
- Adjust-a-fit diameter hand adjustment of 3 ¼" (83) allows flexibility for varying dish sizes
- Adjusting height level is easy and convenient.
- Easy glide design is non-stick for smooth operation
- All 4" swivel casters, 2 with brake, allow easy maneuverability.
- All welded construction increases durability
- Stainless steel material is easy to clean and sanitize
- Dispensers have 25" (635) stacking height capacity



1. **Height Adjustment** – Simply detach or attach springs to adjust tension for the height level you desire.  
2. & 3. **Adjust-a-Fit® Size Adjustment** – Easily re-position and lock the dish guides with a turn of the wrist. No tools necessary!




Model #925

**FACTORY INSTALLED OPTIONS:**

- Bottom perimeter bumper
- 8" (203) one piece vertical handle (except 4 stack)

**ACCESSORIES (PAGE 75):**

- Stainless Steel Dish Covers
- 12" (305) Dispenser Tray available for Models 935, 937 972 and 975



One piece vertical handle

**ELECTRICAL SPECIFICATIONS**

| Model      | W      | A      | V     |
|------------|--------|--------|-------|
| Model #917 | 600 W  | 5.0 A  | 120 V |
| Model #937 | 900 W  | 7.5 A  | 120 V |
| Model #965 | 1350 W | 11.3 A | 120 V |
| Model #927 | 900 W  | 7.5 A  | 120 V |
| Model #975 | 1350 W | 11.3 A | 120 V |
| Model #929 | 1800 W | 15.0 A | 120 V |

208 / 240V, 60 Hz; 220V, 50 Hz also available, please specify.

Freight Class: **92.5**  
Ships in: **4** days or less!



| Model                              | Accommodates Plate Sizes      | Overall Size |           |         |                | Case Weight Lbs. (Kg) | Case Cube Cu. ft. (m³) | Case Cube Cu. ft. (m³) |
|------------------------------------|-------------------------------|--------------|-----------|---------|----------------|-----------------------|------------------------|------------------------|
|                                    |                               | W            | L         | H       | (W L H)        |                       |                        |                        |
| <b>2 Stack - Non-Heated Models</b> |                               |              |           |         |                |                       |                        |                        |
| 905                                | 2-3/4" to 6" (70 to 152)      | 17-1/4"      | 26-1/8"   | 39-1/8" | (438 664 994)  | 85 (38.6)             | 12.9 (.4)              | 12.9 (.4)              |
| 915                                | 4-1/4" to 7-1/2" (108 to 191) | 17-1/4"      | 26-1/8"   | 39-1/8" | (438 664 994)  | 92 (41.7)             | 12.9 (.4)              | 12.9 (.4)              |
| 925                                | 6-1/2" to 9-3/4" (165 to 248) | 17-1/4"      | 30-5/8"   | 39-1/8" | (438 778 994)  | 100 (45.4)            | 14.9 (.4)              | 14.9 (.4)              |
| 935                                | 8-3/4" to 12" (222 to 305)    | 19-1/2"      | 35-1/8"   | 39-1/8" | (495 892 994)  | 115 (52.2)            | 18.9 (.5)              | 18.9 (.5)              |
| <b>3 Stack - Non-Heated Models</b> |                               |              |           |         |                |                       |                        |                        |
| 942                                | 2-3/4" to 6" (70 to 152)      | 17-3/16"     | 38-5/16"  | 39-1/8" | (437 973 994)  | 112 (50.8)            | 18.4 (.5)              | 18.4 (.5)              |
| 952                                | 4-1/4" to 7-1/2" (108 to 191) | 17-3/16"     | 38-5/16"  | 39-1/8" | (437 973 994)  | 120 (54.4)            | 18.4 (.5)              | 18.4 (.5)              |
| 962                                | 6-1/2" to 9-3/4" (165 to 248) | 17-3/16"     | 45-1/16"  | 39-1/8" | (437 1145 994) | 132 (59.9)            | 22.2 (.6)              | 22.2 (.6)              |
| 972                                | 8-3/4" to 12" (222 to 305)    | 19-3/16"     | 51-13/16" | 39-1/8" | (487 1316 994) | 152 (69)              | 27.1 (.8)              | 27.1 (.8)              |
| <b>4 Stack - Non-Heated Models</b> |                               |              |           |         |                |                       |                        |                        |
| 908                                | 2-3/4" to 6" (70 to 152)      | 30-5/8"      | 30-5/8"   | 39-1/8" | (778 778 994)  | 127 (57.6)            | 19.5 (.5)              | 19.5 (.5)              |
| 918                                | 4-1/4" to 7-1/2" (108 to 191) | 30-5/8"      | 30-5/8"   | 39-1/8" | (778 778 994)  | 131 (59.4)            | 19.5 (.5)              | 19.5 (.5)              |
| 928                                | 6-1/2" to 9-3/4" (165 to 248) | 30-5/8"      | 30-5/8"   | 39-1/8" | (778 778 994)  | 153 (69.4)            | 25.8 (.7)              | 25.8 (.7)              |
| <b>2 Stack - Heated Model</b>      |                               |              |           |         |                |                       |                        |                        |
| 917                                | 4-1/4" to 7-1/2" (108 to 191) | 17-1/4"      | 30-5/8"   | 39-1/8" | (438 778 994)  | 113 (51.3)            | 14.9 (.4)              | 14.9 (.4)              |
| 927                                | 6-1/2" to 9-3/4" (165 to 248) | 17-1/4"      | 30-5/8"   | 39-1/8" | (438 778 994)  | 126 (57.2)            | 14.9 (.4)              | 14.9 (.4)              |
| 937                                | 8-3/4" to 12" (222 to 305)    | 19-1/2"      | 35-1/8"   | 39-1/8" | (495 892 994)  | 142 (64.4)            | 18.9 (.5)              | 18.9 (.5)              |
| <b>3 Stack - Heated Models</b>     |                               |              |           |         |                |                       |                        |                        |
| 955                                | 4-1/4" to 7-1/2" (108 to 191) | 17-3/16"     | 45"       | 39-1/8" | (437 1145 994) | 151 (68.5)            | 21.9 (.6)              | 21.9 (.6)              |
| 965                                | 6-1/2" to 9-3/4" (165 to 248) | 17-3/16"     | 45"       | 39-1/8" | (437 1145 994) | 167 (75.8)            | 21.9 (.6)              | 21.9 (.6)              |
| 975                                | 8-3/4" to 12" (222 to 305)    | 19-3/16"     | 51-13/16" | 39-1/8" | (487 1316 994) | 175 (79.4)            | 28.1 (.8)              | 28.1 (.8)              |
| <b>4 Stack - Heated Model</b>      |                               |              |           |         |                |                       |                        |                        |
| 919                                | 4-1/4" to 7-1/2" (108 to 191) | 30-5/8"      | 30-5/8"   | 39-1/8" | (778 778 994)  | 190 (86.2)            | 25.8 (.7)              | 25.8 (.7)              |
| 929                                | 6-1/2" to 9-3/4" (165 to 248) | 30-5/8"      | 30-5/8"   | 39-1/8" | (778 778 994)  | 196 (88.9)            | 25.8 (.7)              | 25.8 (.7)              |

Measurements in ( ) denote metric millimeters, unless otherwise specified. Lake-Glide® Casters: 4" (102) - All swivel, 2 ea. w/brake, extra-load. Heated Models include 6' (1829) coiled cord with 5-15P NEMA (except Model 929 which includes 5-20P) plug for 120 V.) All models 25" (635) plate stacking capacity per dispenser tube.